

# 让工作更轻松!

## POWER

大型制冷设备专用

# 更高极限真空

双重防返油结构

 两档可调气镇

 整体式泵体



强制润滑

VRD-16/24/30 可选配



真空计



波纹管



气门芯拆除工具



推车



型号		VRD-16	VRD-24	VRD-30	VRD-48	VRD-65
抽速m <sup>3</sup> /h(L/S)	50Hz	16(4.4)	24(6.6)	30(8.3)	48(13.8)	65(18)
	60Hz	19.2(5.2)	28.8(7.9)	36(9.9)	57.6(16)	78(21.6)
极限分压力—关闭气镇		4x10 <sup>-2</sup> Pa	4x10 <sup>-2</sup> Pa	4x10 <sup>-2</sup> Pa	4x10 <sup>-2</sup> Pa	4x10 <sup>-2</sup> Pa
极限全压力—关闭气镇		4x10 <sup>-1</sup> Pa	4x10 <sup>-1</sup> Pa	4x10 <sup>-1</sup> Pa	4x10 <sup>-1</sup> Pa	4x10 <sup>-1</sup> Pa
极限全压力—开启气镇		8x10 <sup>-1</sup> Pa	8x10 <sup>-1</sup> Pa	8x10 <sup>-1</sup> Pa	1.5 Pa	1.5 Pa
电源		单相/三相	单相/三相	单相/三相	三相	三相
电机功率		0.75/0.55kW	1.1/0.75kW	1.1kW	1.5kW	2.2kW
进排气口连接口DN		KF25	KF25/40	KF25/40	KF40	KF40
用油量		0.9~1.5L	1.3~2.0L	1.3~2.0L	3.3~4.5L	3.3~4.5L
电机转速 (rpm)	50Hz	1440	1440	1440	1440	1440
	60Hz	1720	1720	1720	1720	1720
工作环境温度		10-40°C	10-40°C	10-40°C	10-40°C	10-40°C
噪音		≤58 dB	≤58 dB	≤58 dB	≤62 dB	≤62 dB
重量		33 kg	36 kg	37 kg	62 kg	65 kg