

Suit for
R32

VALUE[®]
VALUE Creates Value

Making Your Job More Enjoyable

VRR36C4

Recovery Unit



Digital Backlit Display



Purge Function



Brushless DC Technology



Oil-Free Compressors



3 High-Speed Cooling Fans



4-Cylinder

Fastest · Most Powerful

4-Cylinder

- More powerful

Super-Efficient Condenser

- Over-sized micro-channel condenser
- 3 cooling fans

Brushless DC Motor

- More efficient

Large Digital Display

- Easy-to-read large LCD display
- Backlit for clarity

Dual Oil-Free Compressors

- Suitable for all commonly used refrigerants

Model	VRR36C4			
Refrigerant	Categorys III : R12, R134a, R401C, R500, 1234yf Categorys IV : R22, R401A, R401B, R402B, R407C, R407D, R408A, R409A, R411A, R411B, R412A, R502, R509 Categorys V : R402A, R404A, R407A, R407B, R410A, R507, R32			
Power Supply	220-240V~50/60Hz	115V~50/60Hz		
Motor	Brushless DC motor 1.5HP			
Motor Speed	3000 rpm			
Maximal Current Draw	8.5 A	12 A		
Compressor	Oil-less, Air-cooled, Piston style			
Automatic Safety Shut-Off	38.5bar/3850kPa(558psi)			
Recovery Rate (kg/min)		Categorys III	Categorys IV	Categorys V
	Vapor	0.55	0.73	0.72
	Liquid	4.20	5.78	7.63
	Push/pull	8.10	9.00	9.90
Operating Temperature	0 °C -40 °C			
Dimensions	410×275×300 mm			
Weight	19 kg			