

L Series Recovery Unit



Light • Fast

One Key Operation

- Easy to use

High Pressure Protection

- Safe to use

Oil-free Compressor

- Suitable for all commonly used refrigerants

Self-purge Function

- Prevent mixing of various refrigerants

Model	VRR12L-R32			VRR12LOS-R32			
Refrigerant	Categories III : R12, R134a, R401C, R500, 1234fy Categories IV : R22, R401A, R401B, R402B, R407C, R407D, R408A, R409A, R411A, R411B, R412A, R502, R509 Categories V : R402A, R404A, R407A, R407B, R410A, R507, R32						
Power Supply	220V-240V~/50-60Hz	115V~/60Hz	220V-240V~/50-60Hz	115V~/60Hz			
Motor	3/4 HP	3/4 HP	3/4 HP	3/4 HP			
Motor Speed	1450rpm/1750rpm	1750rpm	1450rpm/1750rpm	1750rpm			
Maximal Current Draw	4 A	8 A	4 A	8 A			
Compressor	Oil-less, Air-cooled, Piston style						
Automatic Safety Shut-Off	38.5bar/3850kPa(558psi)						
Recovery Rate (kg/min)	Categories III	Categories IV	Categories V	Categories III	Categories IV	Categories V	
	Vapor	0.20	0.25	0.25	0.20	0.25	
	Liquid	1.60	1.80	2.20	1.60	1.80	2.20
	Push/Pull	4.60	5.60	6.30	4.60	5.60	6.30
Operating Temperature	0 °C-40 °C						
Dimensions	450×250×355 mm						
Weight	13.0 kg			14.2 kg			