

Suit for
R32

VALUE
VALUE Creates Value

Making Your Job More Enjoyable

L Series Recovery Unit



Built in pressure gauge



One key operation



Self-purge function



Oil free compressor



Cooling fan

Light • Fast

One Key Operation

- Easy to use

Twin Cylinder

- Faster recovery

Oil-free Compressor

- Suitable for all commonly used refrigerants

Self-purge Function

- Prevent mixing of various refrigerants

High Pressure Protection

- Safe to use

Model	VRR24L-R32			VRR24LOS-R32			
Refrigerant	Categorys III : R12, R134a, R401C, R500, 1234fy Categorys IV : R22, R401A, R401B, R402B, R407C, R407D, R408A, R409A, R411A, R411B, R412A, R502, R509 Categorys V : R402A, R404A, R407A, R407B, R410A, R507, R32						
Power Supply	220V-240V~/50-60Hz	115V~/60Hz	220V-240V~/50-60Hz	115V~/60Hz			
Motor	1 HP	1 HP	1 HP	1 HP			
Motor Speed	1450 rpm/1750 rpm	1750 rpm	1450 rpm/1750 rpm	1750 rpm			
Maximal Current Draw	5 A	10 A	5 A	10 A			
Compressor	Oil-less, Air-cooled, Piston style						
Automatic Safety Shut-Off	38.5bar/3850kPa(558psi)						
Recovery Rate (kg/min)		Categorys III	Categorys IV	Categorys V	Categorys III	Categorys IV	Categorys V
	Vapor	0.40	0.50	0.50	0.40	0.50	0.50
	Liquid	3.00	3.50	3.50	3.00	3.50	3.50
	Push/Pull	7.50	8.50	9.50	7.50	8.50	9.50
Operating Temperature	0°C-40°C						
Dimensions	450×250×355 mm						
Weight	13.5 kg			14.7 kg			