



VP8DS VP8DSV

Smart Vacuum Pump


NEW

F2L
COMPATIBLE



Vacuum Gauge Compartment

Digital Interface



Automatic Control Valve



Dual-Stage



Bluetooth Connectivity

Smart Evacuation

Oil Health Test Mode for Effective Evacuation

- One-touch oil check in 60 seconds
- Improved oil change practice
- Save money, save time, save environment

Set It and Forget It

- Preset vacuum and decay targets
- Automatic decay testing with on-screen results
- Solenoid valve for vacuum preservation

Remote Vacuum Gauge

- True system vacuum measurement
- Vacuum gauge can be used standalone
- Automatic evacuation and decay test

Dual-Stage

- High ultimate vacuum
- Reliable performance

Bluetooth Connectivity

- Works wirelessly with Hi VALUE App & VMV1S Vacuum Gauge
- On-pump readings

Easy to Use

- Built-in vacuum gauge storage
- Lifting hook
- Prevent oil backflow

Model	VP8DS		VP8DSV
Power Supply	230V~/50-60Hz		230V~/50-60Hz
Flow Rate	8 CFM		8 CFM
	226 L/min		226 L/min
Ultimate Vacuum	Partial Pressure	2x10 ⁻¹ Pa	2x10 ⁻¹ Pa
	Total Pressure	15 micron	15 micron
Pump Design	Dual-stage		Dual-stage
Motor Power	3/4 HP		3/4 HP
Inlet Port	1/4", 3/8", 1/2" SAE		1/4", 3/8", 1/2" SAE
Oil Capacity	426 ml		426 ml
Dimension	355x127x298 mm		355x127x298 mm
Weight	12.5 kg		12.7 kg
Vacuum Gauge	/		VMV1S Vacuum Gauge