

VRP-6DLi

Cordless Vacuum Pump

A2L
COMPATIBLE

NEW



Isolation Ball Valve

Backflow Prevention
Check Valve

Automatic Power
Management

Lifting Hook



High-performance
Li-ion Battery



Brushless DC
Technology



VB918
Battery



Gas Ballast

Cordless • Powerful • Convenient

Faster Evacuation w/ Increased Capacity

- 6 CFM with large oil tank
- Residential and light commercial applications

Compact Design

- Easy to carry
- Easy to store

Automatic Power Management

- Optimized battery performance
- Extended operation up to 1 hour

Dual-Stage

- High ultimate vacuum down to 15 microns

Brushless DC Technology

- Light weight at 9.6 kg
- Highly efficient

Other Features

- Backflow prevention check valve
- Isolation valve & Lifting hook

Model		VRP-6Li
Li-ion Battery		VB918, 18V, 9Ah
Flow Rate		6 CFM
		170 L/min
Ultimate Vacuum	Partial Pressure	2x10 ⁻¹ Pa
	Total Pressure	15 micron
Pump Design		Dual-stage
Motor Power		1/2 HP
Inlet Port		1/4", 3/8", 1/2" SAE
Oil Capacity		417 ml
Dimension		355x127x255 mm
Weight		9.6 kg
Accessory		Carry Bag, VB918 Battery, VAC-1 Battery Charger, Oil Bottle (Oil Not Supplied)